

Agricultural Marketing Service, USDA

§ 58.712

through 19.790,¹ “Definitions and Standards of Identity for Cheese and Cheese Products,” Food and Drug Administration.

(b) *Blend set up.* The trade term for a particular group of vat lots of cheese selected to form a blend based upon their combined ability to impart the desired characteristics to a pasteurized process cheese product.

(c) *Cooker batch.* The amount of cheese and added optional ingredients placed into a cooker at one time, heated to pasteurization temperature, and held for the required length of time.

EQUIPMENT AND UTENSILS

§ 58.706 General construction, repair and installation.

The equipment and utensils used for the handling and processing of cheese products shall be as specified in § 58.128 of this subpart. In addition, for certain other equipment the following requirements shall be met.

§ 58.707 Conveyors.

Conveyors shall be constructed of material which can be properly cleaned, will not rust, or otherwise contaminate the cheese, and shall be maintained in good repair.

§ 58.708 Grinders or shredders.

The grinders or shredders used in the preparation of the trimmed and cleaned cheese shall be of corrosion-resistant material, and of such construction as to prevent contamination of the cheese and to allow thorough cleaning of all parts and product contact surfaces.

§ 58.709 Cookers.

The cookers shall be the steam jacketed or direct steam type. They shall be constructed of stainless steel or other equally corrosion-resistant material. All product contact surfaces shall be readily accessible for cleaning. Each cooker shall be equipped with an indicating thermometer, and shall be equipped with a temperature recording device. The recording thermometer stem may be placed in the cooker if

satisfactory time charts are obtained, if not, the stem shall be placed in the hotwell or filler hopper. Steam check valves on direct steam type cookers shall be mounted flush with cooker wall, be constructed of stainless steel and designed to prevent the backup of product into the steam line, or the steam line shall be constructed of stainless steel pipes and fittings which can be readily cleaned. If direct steam is applied to the product only culinary steam shall be used (see § 58.127(d)).

§ 58.710 Fillers.

A strainer should be installed between the cooker and the filler. The hoppers of all filters shall be covered but the cover may have sight ports. If necessary, the hopper may have an agitator to prevent buildup on side wall. The filler valves and head shall be kept in good repair and capable of accurate measurements. Product contact surfaces shall be of stainless steel or other corrosion resistant material.

QUALITY SPECIFICATIONS FOR RAW MATERIAL

§ 58.711 Cheddar, colby, washed or soaked curd, granular or stirred curd cheese.

Cheese, used in the manufacture of pasteurized process cheese products should possess a pleasing and desirable taste and odor consistent with the age of the cheese; should have body and texture characteristics which will impart the desired body and texture characteristics in the finished product; and should possess finish and appearance characteristics which will permit removal of all packaging material and surface defects. The cheese should at least meet the requirements equivalent to U.S. Standard Grade for Bulk American Cheese for Manufacturing provided the quantity of the cheese with any one defect as listed for U.S. Standard Grade is limited to assure a satisfactory finished product.

§ 58.712 Swiss.

Swiss cheese used in the manufacture of pasteurized process cheese and related products should be equivalent to U.S. Grade B or better, except that the cheese may be blind or possess finish

¹21 CFR Part 18 was redesignated as Part 131 at 42 FR 14302, Mar. 15, 1977.

§ 58.713

characteristics which do not impair the interior quality.

§ 58.713 Gruyere.

Gruyere cheese used in the manufacture of process cheese and related products should be of good wholesome quality and except for smaller eyes and sharper flavor shall meet the same requirements as for Swiss cheese.

§ 58.714 Cream cheese, Neufchatel cheese.

These cheeses when mixed with other foods, or used for spreads and dips should possess a fresh, pleasing and desirable flavor.

§ 58.715 Cream, plastic cream and anhydrous milkfat.

These food products shall be pasteurized, sweet, have a pleasing and desirable flavor and be free from objectionable flavors, and shall be obtained from milk which complies with the quality requirements as specified in §§ 58.132 through 58.138 of this subpart.

§ 58.716 Nonfat dry milk.

Nonfat dry milk used in cheese products should meet the requirements equivalent to U.S. Extra Grade except that the moisture content may be in excess of that specified for the particular grade.

§ 58.717 Whey.

Whey used in cheese products should meet the requirements equivalent to USDA Extra Grade except that the moisture requirement for dry whey may be waived.

§ 58.718 Flavor ingredients.

Flavor ingredients used in process cheese and related products shall be those permitted by the Food and Drug Standards of Identity, and in no way deleterious to the quality or flavor of the finished product. In the case of bulky flavoring ingredients such as pimento, the particles should be, to at least a reasonable degree, uniform in size, shape and consistency. The individual types of flavoring materials should be uniform in color and should impart the characteristic flavor desired in the finished product.

7 CFR Ch. I (1-1-01 Edition)

§ 58.719 Coloring.

Coloring shall be Annatto or any other cheese or butter color which is approved by the Food and Drug Administration.

§ 58.720 Acidifying agents.

Acidifying agents if used shall be those permitted by the Food and Drug Administration for the specific pasteurized process cheese product.

§ 58.721 Salt.

Salt shall be free flowing, white refined sodium chloride and shall meet the requirements of The Food Chemical Codex.

§ 58.722 Emulsifying agents.

Emulsifying agents shall be those permitted by the Food and Drug Administration for the specific pasteurized process cheese product, and shall be free from extraneous material.

OPERATIONS AND OPERATING PROCEDURES

§ 58.723 Basis for selecting cheese for processing.

A representative sample shall have been examined to determine fat and moisture content. One sample unit from each vat of cheese shall have been examined to determine the suitability of the vat for use in process cheese products in accordance with the flavor, body and texture characteristics permitted in §§ 58.711 through 58.714 as applicable, and to determine the characteristics it will contribute to the finished product when blended with other cheese. The cheese included in each blend shall be selected on the basis of the desirable qualities which will result in the desired finished product. Recook from equivalent blends may be used in an amount that will not adversely affect the finished product. Hot cheese from the filler may be added to the cooker in amounts which will not adversely affect the finished product.

§ 58.724 Blending.

To as great an extent as is practical, each vat of cheese should be divided and distributed throughout numerous cooker batches. The purpose being to